

KENWOOD

Listen to the Future



TK-7360(H)/8360(H)

VHF/UHF Compact FM Mobile Radios

FleetSync[®]
by KENWOOD



GPS

Kenwood's TK-7360/8360 extra-wide bandwidth mobiles cover all available channels for your organizations requirements. The employee-friendly front consoles boast a bright backlit 10-character display providing clear presentation of messages, caller identification, GPS location and radio channel information day or night. The 10 programmable function keys allow fleet mobiles to be customized to fit the needs of the various user types and departments.

128 X 128 CAPACITY

Even the largest of organizations can be accommodated with the 128 Channel and 128 Zone capacities. Channels are logically organized by districts, regions, departments and workgroups with no learning curve for immediate easy use.

WORLD-CLASS AUDIO

Kenwood, a world renowned leader in audio and communications electronics, utilizes its expertise to provide best-of-class audio performance undeniably clearer and crisper than any other brand of two-way radio equipment.

INSTALLATION INTERFACES

All Kenwood mobiles are ready to interface into any type vehicular or fixed station installation. The DB15 interface provides features including Ignition Sense (automatic power on/off with ignition key), External Switch (for light bars, equipment, etc.) and Horn Alert (alerts extravehicular workers of incoming calls with horn or lights). The optional KCT-60M cable provides other interfaces including data I/O's for equipment such as hardened GPS installations and vehicle engine sensors.

POWER CONTROL

The transmit power is PC programmable per channel (5, 25 or 45/50 Watts) to comply with any licensing or system design requirements.

CUSTOMIZE

The 10 pc programmable function keys permit simple or advance customization of the front panel controls for both fixed control stations and vehicular installations. Typical functions such as channel scan, channel monitor and talk around, and specialty functions such as selective call, emergency, GPS Send, messaging are all instantly accessible and display indicated.

SHORT TEXT MESSAGING

The FleetSync[®] Status Messaging permit sending/receiving canned text messages conserving airtime and simplifying repetitive routine communications. Designated messages can trigger external devices as a gate, lock or valve for remote control applications.

ALL SYSTEM SIGNALLING

FleetSync[®]

Kenwood's FleetSync[®] digital suite provides built-in programmable PTT ID, Caller ID Display, Short /Long Text Messaging, canned Status Messaging, Emergency, Radio Check, Stun/Revive, Selective Calling, Remote Control and GPS AVL capabilities for efficient managed dispatch operations and remote control applications. FleetSync[®] is available across the Kenwood product line so your organization can utilize it on all tier radios. FleetSync[®] compatible dispatch and AVL products are available from a multitude of manufacturers.

MDC-1200

In addition to FleetSync[®], for systems utilizing MDC-1200, PTT ID, Caller ID Display, Stun/Revive, Radio Check and Emergency are available.

Emergency

For hazardous and hostile-duty environments an emergency alert can be sent to the dispatcher or other group members in FleetSync[®], MDC-1200 or DTMF.

QT/DQT, DTMF & TWO-TONE

The QT/DQT sub-audible toned/coded squelch eliminates annoying and confusing voice chatter from other talk groups. DTMF encode/decode provides PTT identification, telephone calling, selective call alerting and remote control. Two-tone encode/decode is also provide for legacy fire alerting and remote door applications.

COLOR SAFETY

Transmit, receive and selective call alerts are indicated with a standard tri-color LED (red, green, amber). The blue LED can be programmed to get the users attention of an incoming priority voice call or important selective call alert. While driving, peripheral vision safely catches the call even if the volume is turned down.



GPS AVL

GPS options transmit accurate vehicle location, heading and speed information to your dispatch centers for fleet tracking, best routing and employee safety.

VOICE STORAGE & GUIDE

The VGS-1 option provides zone/channel number announcement for "no look" zone/channel changes. Drivers can playback missed voice calls upon returning to the vehicle saving eliminating lost time and revenue. GPS data can be stored for management post review in the event communications was impaired or a mapping system was not generally used.

MORE FEATURES

- Multiple Scan Functions •Priority Scan •Scan Del/Add Vote
- Search (automatic repeater search & selection) •BCL (Busy Channel Lockout) •Talk Around •Time-out Timer •Companded Audio (per CH / narrow & wide) •Voice Inversion Scrambler (per CH)*1
- Minimum Volume •Operator Selectable Tone •Horn Alert Function •Password Protection Embedded Message
- 8 Programmable Accessory Ports •Kenwood ESN (Electronic Serial Number) •Microphone Gain Adjust (High/Normal/Low)
- Microsoft Windows[®] PC Programming & Tuning

*1 This function may not be permitted in certain countries. Please contact your Kenwood dealer for further information.



Options

■ **KMC-35**
Microphone



■ **KMC-9C**
Desktop Microphone



■ **KLF-2**
Line Filter



■ **KMC-36**
Keypad Microphone



■ **KES-3**
External Speaker



■ **KCT-18**
Ignition Sense Cable
(requires KCT-60 option)



■ **KMC-30**
Microphone



■ **KES-5**
External Speaker



■ **KCT-36**
3m Extension Cable
(for KCT-60)



■ **KMC-32**
16-key Keypad
Microphone



■ **KMB-10**
Key Lock Adapter



■ **KCT-60**
Connection Cable



■ **VGS-1**
Voice Storage Unit
(uses 26p connector)



All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Specifications

	TK-7360	TK-7360H	TK-8360	TK-8360H
GENERAL				
Frequency Range	136~174 MHz		450~520 MHz	
Type 1	-		400~470 MHz	
Type 2	-		-	
Number of Channels/Zones	128 / 128		128 / 128	
Channel Spacing	25 kHz / 12.5 kHz		25 kHz / 12.5 kHz	
Wide / Narrow	25 kHz / 12.5 kHz		25 kHz / 12.5 kHz	
Operating Voltage	13.6 V DC±15 %		13.6 V DC±15 %	
Current Drain	-		-	
Standby	0.4 A	0.4 A	0.4 A	0.4 A
Receive	1.0 A	1.0 A	1.0 A	1.0 A
Transmit (M/H)	8.0 A	14.0 A	8.0 A	14.0 A
Operating Temperature Range	-22 °F ~ +140 °F (-30 °C ~ +60 °C)		-22 °F ~ +140 °F (-30 °C ~ +60 °C)	
Frequency Stability	±2.5 ppm (-22 °F ~ +140 °F)		±2.5 ppm (-22 °F ~ +140 °F)	
Antenna Impedance	50 Ω		50 Ω	
Dimensions (W x H x D)	6.29 x 1.69 x 5.35 in		6.29 x 1.69 x 5.35 in	
Projections not included	(160 mm x 43 mm x 136 mm)		(160 mm x 43 mm x 136 mm)	
Weight (net)	4.4 lbs. (2.0 kg)		4.4 lbs. (2.0 kg)	

Kenwood reserves the right to change specifications and features without prior notice.
FleetSync® is a registered trademark of Kenwood Corporation.
Windows® is a registered trademark of Microsoft Corporation in the United States and other countries.

	TK-7360	TK-7360H	TK-8360	TK-8360H
RECEIVER (Measurements made per EIA/TIA-603)				
Sensitivity (12dB SINAD)	-		-	
Wide	0.28 μV		0.28 μV	
Narrow	0.35 μV		0.35 μV	
Selectivity	-		-	
Wide	75 dB		75 dB	
Narrow	65 dB		65 dB	
Intermodulation Distortion	-		-	
Wide	70 dB		70 dB	
Narrow	70 dB		70 dB	
Spurious Response	75 dB		75 dB	
Audio Output (4 Ω impedance)	4 W with less than 5 % distortion		4 W with less than 5 % distortion	
TRANSMITTER (Measurements made per EIA/TIA-603)				
RF Power Output	5 W ~ 25 W	5 W ~ 50 W	5 W ~ 25 W	5 W ~ 45 W
Spurious Response	70 dB		70 dB	
Type of Emission	-		-	
Wide	16K0F3E		16K0F3E	
Narrow	11K0F3E		11K0F3E	
FM Hum & Noise	-		-	
Wide	45 dB		45 dB	
Narrow	40 dB		40 dB	
Microphone Impedance	600 Ω		600 Ω	
Audio Distortion	-		-	
Wide	3 %		3 %	
Narrow	5 %		5 %	

Applicable MIL-STD & IP

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain*1	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog*1	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust*1	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, III, V	516.3/Procedure I, IV, V	516.4/Procedure I, IV, V	516.5/Procedure I, IV, V	516.6/Procedure I, IV, V

International Protection Standard

Dust & Water Protection IP54*1

*1: Necessary conditions are: (1) KMC-35/36 microphone is connected; (2) cap is installed on speaker connector; (3) cover is installed on D-sub 15-pin connector; and (4) neither KCT cable nor SP cable is connected.

Listen to the Future

Kenwood has always connected with people through sound. Now we want to expand the world of sound in ways that only Kenwood can, listening to our customers and to the pulse of the coming age as we head toward a future of shared discovery, inspiration and enjoyment.

Kenwood U.S.A. Corporation

Communications Division Headquarters

3970 Johns Creek Court, Ste. 100 Suwanee, GA 30024, U.S.A



CL699K-E-2